

Index

- Abbe number, 18
 - for the infrared spectra, 115
- aberrations, 116
 - chromatic, 18
- achromats, 39
- air-spaced
 - doublet, 65
 - triplet, 65
- Airy disk, 113
- AMTIR-1, 58
- aspherizing, 23, 52
 - a singlet, 26
- astigmatism, 19, 104
- athermats, 73

- ball lens, 89
- bending a lens, 11
- best shape, 11
 - for minimum spherical aberration, 23

- Cassegrain
 - basic telescope layout, 122
 - classic system, 124
 - with two spherical mirrors, 123
- chromatic aberration, 18
- cold stop, 67
- coma, 19
- curvature, 11

- Dall-Kirkham arrangement, 124
- detector, 16, 21
- Dewar housing, 67
- dialyte, 57
- diamond-turned hybrid, 50
- diffraction limit, 113
- diffractive phase profile, 52

- $f/\#$, 115
- focal plane array, 148

- focus shift
 - of a diffractive lens, 74
 - of a refractive element, 73
- frequency
 - cut-off, 147
 - normalized, 147
 - Nyquist, 149
 - spatial, 147

- Gregorian
 - microscope objective, 130
 - telescope, 127
- G-sums, 15

- half field angle, 115
- hybrid, 69
 - lens, 151
 - petzval objective, 67

- image height, 115
- impact of housing material, 80

- limits, 147
- lens
 - thick, 34
 - thin, 11
- LWIR region, 50

- manufacturing remarks, 109
- materials for the 3–5 μm spectral band (MWIR), 77
- materials for the 8–12 μm spectral band (LWIR), 78
- microscope objectives, 121
- minimum blur, 17
- multiple lens arrangement, 23
- MWIR region, 48

- n , 12
- net curvature, 11

- Newton, Isaac, 121
- nomograms, 55
- Nyquist frequency, 149

- optical modulation transfer function, 147

- parabolic mirror, 107
- paraxial focal plane, 21
- Pegel diagrams, 95, 98
- performance plots, 59
- Petzval
 - curvature, 101
 - objective, 65
- phase
 - coefficients, 61
 - equation, 76
- pixel sizes, 147, 148
- plane-parallel plate, 137
- power, 11
- prisms, 137

- relative aperture, 113
- reversed telephoto, 62
- Ritchey-Chretien configuration, 125

- sapphire, 141

- Seidel
 - diagrams, 95
 - surface contributions, 96
- shift of image, 141
- silicon, 141
- single optical elements, 113
- single-imaging mirror, 101
- single-point diamond turning, 108, 109, 128
- slow tool servo, 108
- Smith's method, 45
- spherical aberration, 16

- telephoto, 62
- telescope objectives, 121
- thermal glass constant, 74
- thick lens, 34
- thin lens, 11
 - concept, 33
- toroidal mirrors, 104
- transverse spherical-aberration contribution, 12
 - third-order, 35
- tunnel diagrams, 139
- two Schwarzschild objectives, 131
- two separated components, 57
- two-mirror systems, 121

About the Author



Max J. Riedl was born in Kempten, Germany, where he was educated at the Mathematisch Mechanisches Institut. He also graduated from the Akademie für angewandte Technik in Munich, where he studied precision mechanics and optics. He has worked in the field of mathematical and optical instruments for many years and holds numerous patents for mechanical, optical, and electro-optical devices. He held technical as well as business leadership positions during the 45 years he lived in the United States. He has published and presented many papers on fundamental lens design as well as on replicating optical elements and diamond turning diffractive optical components for applications in the infrared spectrum. He regularly teaches short courses on these subjects. He is the author of the well-received tutorial text *Optical Design Fundamentals for Infrared Systems* (SPIE Press, Vol. TT48), which is now in its second edition. He has also translated that textbook into German. He is a Fellow of SPIE. Presently, he resides in Bavaria, Germany.